

ACT-206D Embedded DIN-rail Communication Manager



◆ Specifications

Model	ACT-206D	Wireless Communication	GPRS (Option)
CPU		Others	
Default Configuration	ARM® Cortex®-A8 600MHz	Operating System	Embedded Linux (gcc 4.3.2)
Memory		RTC	Real Time Clock (Option)
Default Configuration	256MB DDR2	Alarm	Buzzer
Storage		Serial ID	License Management
NAND FLASH	256MB	Automatic Restart	Watchdog
Expansion	1 × TF Slots	Trigger	
Status Lamp		Reset	Manual Reset Button
Power	1 × PWR	Power	
Run	1 × RUN	Input	12VDC (2 PIN terminal, anti-reverse protection)
LAN	2 × Link、ACT	Typical Power Consumption	3.5W
Serial Port	6 × Serial Data	Environmental	
Others	2 × GPIO (custom settings)	Operating Temperature	-40~70℃
Communication Interface		Storage Temperature	-40~85℃
LAN	2 × 10/100M (RJ45), 1.5KV electromagnetic isolation	Relative Humidity	20~90% (non-condensing)
Serial Port	2 × RS-232/485 (terminal), 2KV photoelectric isolation	Mounting	DIN-rail Mounting
USB	4 × RS-485 (terminal, support ADCC), 2KV photoelectric isolation	Dimensions (W×H×D)	60mm × 160mm × 124mm
	2 × USB 2.0 (internal)		

◆ Ordering Information

ACT-206D

Embedded DIN-rail Communication Manager, 2 × 10/100M LAN, 2 × RS-232/485, 4 × RS-485.

ACT-206DG

Embedded DIN-rail Communication Manager, 2 × 10/100M LAN, 2 × RS-232/485, 4 × RS-485, GPRS / LTE-4G.



Shanghai Nematron Technology Co., Ltd.

245 Xinjun Ring Road, Suite D302 Caohejing Pujiang Hi-Tech Park, Shanghai 201114, China

Tel: +86 21 5109 6600

Fax: +86 21 5426 3008