

Fomax F9107 Panel PC



◆ Specifications

Model		Fomax F9107
Basic Configuration		
CPU	Intel® Core™ i3 3.2GHz, 3M Cache, 64 Bit, Dual-Core (Standard) 6th & 7th Intel® Core™ i3/i5/i7/Pentium®/Celeron® CPU series, LGA1151 Socket (Option)	
Chipset	Intel® Q170	
Memory	1×4GB DDR4 SODIMM (2×SODIMM), Max. 32GB	
Storage	1×500GB, With 24×7 operation (Standard) HDD (2.5"), SSD (Option)	
Expansion Slots	1×PCI-Ex4, 1×Mini-PCle (full-size)	
I/O Interface	Standard: 2×RS-232/422/485 (rear); 4×RS-232 (Internal, optional external) Standard: 4×USB 3.0 (rear); 2×USB 2.0 (Internal, optional external) 4×SATA 3.0 (support RAID 0/1/5/10) 1×SIM Card Holder 2×10/100/1000M 1×HDMI, 2×Display-Port 1×Line In, 1×Line Out, 1×Mic Power Switch, Power LED, Power Interface	
Video Memory	On board, DVMT	
Drivers		
Option	External USB DVD-ROM or DVD-RW	
Monitoring		
Watchdog	0~255 Sec	
Displays		
Type	19" SXGA TFT LCD	
Resolution	1280×1024	
Brightness	250cd/m ²	
Contrast Ratio	1000:1	
Viewing Angle	170° (H), 160° (V)	
Backlight	LED	
Touchscreen	5-wire resistive type (Standard)	
Power		
Power Input	100~240VAC	
Mechanical Specifications		
Cooling	Active with fan	
Construction	Aluminum Front Panel & Stainless Steel Panel, VESA	
Mounting		
Dimensions (W×H×D)	464mm×375mm×90mm	
Cutout Size (W×H)	403mm×331mm	
Weight	8.7kg	
Environmental		
Operating Temperature	0~50°C	
Storage Temperature	-0~70°C	
Relative Humidity	10~85% (non-condensing)	
IP Rating	IP65 compliant front panel	
Certification	FCC, CE	



Shanghai Nematron Technology Co., Ltd.

245 Xinjun Ring Road, Suite D302 Caohejing Pujiang Hi-Tech Park, Shanghai 201114, China

Email: marketing@nematron.com.cn