

## Fomax S1501 Flat Panel PC



### ◆ Specifications

Model		Fomax S1501	Type	15" XGA TFT LCD
<b>Basic Configuration</b>			<b>Resolution</b>	1024×768
<b>CPU</b>	Onboard Intel® Core™ i5-6200U 2.3GHz, up to 2.8GHz, 3M Cache, 64 Bit, Dual-Core		<b>Brightness</b>	420cd/m <sup>2</sup>
	<b>Memory</b>	4GB DDR3L SODIMM (1×SODIMM), Max. 8GB	<b>Contrast Ratio</b>	800:1
<b>Storage</b>		1×500GB, With 24×7 operation (Standard)	<b>Viewing Angle</b>	160° (H), 160° (V)
	<b>Expansion Slots</b>	HDD (2.5"), SSD, mSATA (Option)	<b>Backlight</b>	LED
<b>I/O Interface</b>		2×Mini-PCle (full-size, one share with mSATA)	<b>Touchscreen</b>	5-wire resistive type (Standard)
	<b>Video Memory</b>	4×RS-232 (COM1~4), 1×RS-232/485 (COM6)	<b>Power</b>	
<b>Drivers</b>		2×USB 3.0, 2×USB 2.0	<b>Power Input</b>	12VDC Input (2 Port terminal), with power adapter
	<b>Option</b>	1×SATA 3.0, 1×mSATA	<b>Mechanical Specifications</b>	
<b>Monitoring</b>		2×10/100/1000M	<b>Cooling</b>	Fanless
	<b>Watchdog</b>	1×VGA, 1×HDMI	<b>Construction</b>	Aluminum Front Panel & Steel Panel, VESA
<b>Displays</b>		Power Switch, Power LED, Power Interface	<b>Mounting</b>	Aluminum Front Panel & Steel Panel, VESA
	On board, DVMT		<b>Dimensions (W×H×D)</b>	369mm×301mm×85mm
<b>Option</b>		External USB DVD-ROM or DVD-RW	<b>Cutout Size (W×H)</b>	353mm×283mm
<b>Monitoring</b>			<b>Environmental</b>	
<b>Watchdog</b>		0~255 Sec	<b>Operating Temperature</b>	0~50°C
<b>Displays</b>			<b>Storage Temperature</b>	-20~70°C
			<b>Relative Humidity</b>	10~85% (non-condensing)
			<b>IP Rating</b>	IP65 compliant front panel
			<b>Certification</b>	FCC, CE



**Shanghai Nematron Technology Co., Ltd.**

245 Xinjun Ring Road, Suite D302 Caohejing Pujiang Hi-Tech Park, Shanghai 201114, China

Tel: +86 21 5109 6600

Fax: +86 21 5426 3008