

## PR-17&19xx Multi-port Combo LCD KVM Console



### ◆ Specifications

Model	PR-1708	PR-1716	PR-1908	PR-1916
<b>Computer Connections</b>				
Direct	8	16	8	16
Maximum	256	512	256	512
<b>LCD Monitor</b>				
View area	17"		19"	
LED model	SXGA TFT			
Optimum resolution	1280 × 1024 @60Hz			
Display color	16.7 M			
Pixel pitch	0.264mm × 0.264mm		0.294mm × 0.294mm	
Viewing angle	170°(H), 160°(V)			
Luminance	250cd/m <sup>2</sup>			
Contrast ratio	1000:1			
Response time	5ms			
Backlight	LED			
LCD operating life	30,000 hrs			
<b>Keyboard</b>				
Keypress Design	99 keys(82 keys main keyboard + 17 independent small numeric keyboard)			
<b>Mouse</b>				
X/Y resolution	>1000 points/inch, (40 points/mm)			
Touchpad	Support			
<b>Keyboard &amp; Mouse</b>				
Port	PS/2 or USB			
Operating System	Support Windows, Linux, Mac and Sun			
Lifetime	>1,000,000 times			
<b>Port Selection</b>				

<b>Switching</b>	Front panel pushbuttons, hotkeys, OSD menu			
<b>Power</b>				
<b>Input power</b>	100~240Vac, 50~60Hz, <1.5A			
<b>Power consumption</b>	17W	23W	21W	23W
<b>Environmental</b>				
<b>Operating Temperature</b>	0~40°C			
<b>Storage Temperature</b>	-20~60°C			
<b>Relative Humidity</b>	0~80% (non-condensing)			
<b>Dimensions (W×H×D)</b>	448mm×42.5mm×581mm		448mm×42.5mm×605mm	
<b>Weight</b>	13.3kg	13.7kg	13.5kg	13.7kg
<b>Certification</b>	FCC, CE, 3C		3C	



**Shanghai Nematron Technology Co., Ltd.**  
 245 Xinjun Ring Road, Suite D302 Caohejing Pujiang Hi-Tech Park, Shanghai 201114, China  
 Tel: +86 21 5109 6600 Fax: +86 21 5426 3008