

## RAC-MIL15 Rugged Portable



### ◆ Specifications

Model		RAC-MIL15	
<b>Basic Configuration</b>			
CPU	Intel® Core™ i5 2.2GHz (standard)	Others	
	6th Intel® Core™ i3/i5/i7/Pentium®/Celeron® Processor, LGA1151 Socket (option)		
Memory	8GB	Operating system	Support Windows 7 / 8 / 10
Storage	128GB 2.5" SSD	Keyboard & mouse	US 86 key rubber keyboard IP65 with protective indicator lamp and mouse button
Slots	3×PCI, 2×PCI-Ex16	<b>Mechanical Specifications</b>	
I/O Interface	1×RS-232 (internal, optional for UPS)	Construction	Anti-corrosion Aluminum Shell Reinforcement Cabinet
	1×USB 2.0 (external connection via aviation Plug)	Dimensions (W×H×D)	480mm×210mm×470mm
Video Memory	1×10/100/1000M (external connection via aviation Plug)	Weight	20.05kg
	On board, DVMT	<b>Environmental</b>	
Driver	DVD-ROM (Ultra-thin suction)	Operating Temperature	-20~60°C (standard), -40~65°C (option)
Option	DVD-ROM (Ultra-thin suction)	Storage Temperature	-40~70°C
<b>Monitoring</b>			
Watchdog	0~255 Sec	Relative Humidity	10~90% (non-condensing)
<b>Display</b>			
Display type	15.4" WXGA TFT LCD	Shock (Operating)	15g, 11ms
Resolution	1280×800	Shock (Storage)	20g, 11ms
<b>Power</b>			
Default Configuration	200W, 110~230V AC and 10~32V DC, Military Regulation Closed Power Connector	Protection level	IP54 / 65 protection when the entire system is working
UPS	Built-in UPS, 10 to 20 minutes, depending on load	Warranty period	5 years
		Certification	FCC, CE



**Shanghai Nematron Technology Co., Ltd.**

245 Xinjun Ring Road, Suite D302 Caohejing Pujiang Hi-Tech Park, Shanghai 201114, China

Tel: +86 21 5109 6600

Fax: +86 21 5426 3008