

SE401D Rackmount Server



◆ Specifications

Model	SE401D
CPU	
Default Configuration	2×Intel® Xeon® 1.8GHz, 10M Cache, 64 Bit, Quad-Core
Option	Intel® Xeon® E5-2400/E5-2400 V2 CPU series (LGA1356 Socket)
Chipset	
Southbridge	Intel® C602
Memory	
Default Configuration	2×2GB REG ECC DDR3 (8×DIMM, Support three channels)
Max.	128GB
Slots	
PCI-Ex16	1
PCI-Ex8	2 (w/ x4 Link), 1 (w/ x8 Link)
PCI	1
Storage	
Default Configuration	1×1TB (64M Cache, With 24×7 operation)
Option	HDD (3.5"), SSD
Driver	
Default Configuration	DVD-ROM
Option	DVD-RW
I/O Interface	
Serial Port	1×RS-232 (rear), 1×RS-232 (internal lead to external)
USB	Standard: 7×USB 2.0 (2 front, 4 rear, 1 Internal Type-A)
SATA	4×SATA 2.0, 2×SATA 3.0 (support

Ethernet	RAID0/1/5/10) 2×10/100/1000M (Intel® Network Chip)
Audio	No
K&M Port	USB
Display	
Video Port	1×VGA
Video Memory	16MB
Monitoring	
Watchdog	0~255 Sec
Power	
Default Configuration	ATX PS2 power
Option	Redundant power supply
Others	
Keyboard & Mouse	Standard: USB Keyboard & 3D USB Mouse
Environmental	
Operating Temperature	0~50°C
Storage Temperature	-20~70°C
Relative Humidity	5~95% (non-condensing)
Vibration	1.5g
Shock	10g
MTBF	50,000 hrs
Dimensions (W×H×D)	483mm×177mm×510mm
Chassis	Black panel, 2×12cm ball bearing fans, 93CFM
Certification	FCC, CE



Shanghai Nematron Technology Co., Ltd.

245 Xinjun Ring Road, Suite D302 Caohejing Pujiang Hi-Tech Park, Shanghai 201114, China

Tel: +86 21 5109 6600

Fax: +86 21 5426 3008