

Smart T6205 Emedded IPC



◆ Specifications

Model	Smart T6205		Audio	1×Line-In, 1×Line-Out, 1×Mic
CPU	Intel® Core™ i3 2.1GHz, 3M Cache, 64 Bit, Dual-Core		K&M Port	1×PS/2 Keyboard & Mouse (share with Y-Cable)
Default Configuration	2nd & 3rd Intel® Core™ i3/i5/i7/Pentium®/Celeron® Mobile Processor (PGA988 Socket)		Display	
Option			Video Port	1×VGA, 1×DVI-D, 1×HDMI
Chipset	Intel® QM77		Video Memory	On board, DVMT
Southbridge			Monitoring	
Memory	2GB DDR3 SODIMM (2× DDR3/DDR3L SODIMM), Max. 16GB		Watchdog	0~255 Sec
Default Configuration	2×PCI or 1×PCI, 1×PCI-Ex16		Power	
Slots	1×full-size		Default Configuration	100~240VAC, 1.5A, 50 / 60MHz; 12VDC, 7A (power adapter) DC-in: 12VDC
PCI or PCIe	2×PCI or 1×PCI, 1×PCI-Ex16		Mechanical Specifications	
Mini-PCIe	1×full-size		Cooling	Fanless
Storage	1×500GB (With 24×7 operation)		Construction	Aluminum & Steel
Default Configuration	HDD (2.5"), SSD, mSATA		Mounting	Desktop, Wallmount
Option			Dimensions (W×H×D)	299mm×95.8mm×220mm
I/O Interface			Environmental	
Serial Port	2×RS-232/422/485 (COM1: rear), 3×RS-232 (COM2/3/4: front)		Operating Temperature	0~60℃
USB	6×USB 2.0 (2 front, 4 rear), 2×USB 3.0 (rear)		Storage Temperature	-10~70℃
SATA	2×SATA 2.0, 2×SATA 3.0, 1×mSATA		Relative Humidity	10~95% (non-condensing)
LAN	2×10/100/1000M (rear)		Certification	FCC, CE
GPIO	8-Bit (4-in/4-out)			



Shanghai Nematron Technology Co., Ltd.

245 Xinjun Ring Road, Suite D302 Caohejing Pujiang Hi-Tech Park, Shanghai 201114, China

Tel: +86 21 5109 6600

Fax: +86 21 5426 3008