

WM350 Series Compact IPC



◆ Specifications

Model	WM351E	WM354	WM355
CPU			
Default Configuration	Intel® Core™ i3 3.3GHz, 3M Cache, 64 Bit, Dual-Core	Intel® Core™ i3 3.4GHz, 3M Cache, 64 Bit, Dual-Core	Intel® Core™ i3 3.7GHz, 3M Cache, 64 Bit, Dual-Core
Option	Intel® Core™ i3/i5/i7/Pentium®/Celeron® CPU Series (LGA1155 Socket)	4th Intel® Core™ i3/i5/i7/Pentium®/Celeron® CPU Series (LGA1150 Socket)	6th Intel® Core™ i3/i5/i7/Pentium®/Celeron® CPU Series (LGA1151 Socket)
Chipset			
Southbridge	Intel® H61	Intel® H81	Intel® H110
Memory			
Default Configuration	2GB DDR3 (2×DIMM, Support dual-channel)	2GB DDR3 (2×DIMM, Support dual-channel)	4GB DDR4 (2×DIMM, Support dual-channel)
Max.	16GB	16GB	32GB
Slots			
PCI	0	2	2
PCI-Ex1	3	0	1
PCI-Ex4	0	1	0
PCI-Ex16	1	1	1
Mini-PCIe	0	0	1 (full-size)
Sim	0	0	1
Storage			
Default Configuration	1×1TB (64M Cache, With 24×7 operation)		
Option	HDD (3.5"), SSD		
I/O Interface			
Serial Port	Standard: 2×RS-232 (front), 1×422/485, 1×RS-232 (internal lead to external); 2×RS-232 (internal optional)	Standard: 1×RS-232/422/485 (front), 1×RS-232/422/485, 1×RS-232 (internal lead to external); 7×RS-232 (internal optional)	Standard: 1×RS-232/422/485, 1×RS-232 (front), 2×RS-232 (internal lead to external); 6×RS-232 (internal optional)
USB	Standard: 4×USB 2.0 (front); 6×USB 2.0 (internal optional)	Standard: 4×USB 2.0, 2×USB 3.0 (front); 2×USB 2.0 (internal optional)	Standard: 2×USB 2.0, 4×USB 3.0 (front); 3×USB 2.0 (internal optional)

SATA	4×SATA 2.0	1×SATA 2.0, 2×SATA 3.0, 1×mSATA	3×SATA 3.0, 1×M.2
Ethernet	2×10/100/1000M	2×10/100/1000M (Intel® Network chip)	2×10/100/1000M
Audio	1×Line-in, 1×Line-out, 1×Mic-in		
K&M Port	1×PS/2 Keyboard, 1×PS/2 Mouse	USB	
Display			
Video Port	1×VGA, 1×DVI-D	1×VGA, 1×DVI-D, 1×HDMI, 1×DisplayPort	1×VGA, 1×DVI-D, 1×HDMI
Video Memory Option	On board, DVMT Pluggable PCI-Ex16 graphics card		
Monitoring			
Watchdog	0~255 Sec		
Power			
Default Configuration	ATX 1U Power		
Others			
Keyboard & Mouse	PS/2 Keyboard & 3D USB Mouse	USB Keyboard & 3D USB Mouse	
Environmental			
Operating Temperature	0~50℃		
Storage Temperature	-20~70℃		
Relative Humidity	5~95% (non-condensing)		
Vibration	1Grms (5~500Hz)		
Shock	10G (half sine 11ms)		
MTBF	50,000 hrs		
Dimensions (W×H×D)	320mm×164mm×316mm		
Mounting	Desktop, Wallmount		
Certification	FCC, CE,		



Shanghai Nematron Technology Co., Ltd.

245 Xinjun Ring Road, Suite D302 Caohejing Pujiang Hi-Tech Park, Shanghai 201114, China

Tel: +86 21 5109 6600

Fax: +86 21 5426 3008